

Product/Technical Data Sheet

Fenta™ Ceiling Tiles

April 2021

PRODUCT CHARACTERISTICS

Fenta Ceiling Tiles are a 4.5 mm and 6mm thick fibre cement base tile that weigh 5.04 kg. The Tiles are coated with a two-pack white (non-yellowing) polyurethane finish suitable for use in a 1200mm x 600mm modular suspended two-way ceiling grid system.

COMPOSITION

Surface Coating

- Face Surface – a primer coat and two coats Polyurethane full gloss finish.\
- Reverse face and edges – sealed with primer coat

Base

- Cellulose fibre
- Portland cement
- Ground sand and water

DURABILITY

Fenta Ceiling Tiles use the patented UltraLight™ Technology – a UV curing process that coats products with a finish of premium quality and outstanding durability.

Within the normal range of applications, the life of the product is limited only by the durability of the supporting structure and the materials used in the fixing.

Fenta Ceiling Tiles have excellent durability, hardness and chemical resistance, and meet all current domestic and overseas hygiene regulations, when installed correctly.

Fenta Ceiling Tiles are:

- Hard wearing and scratch resistant
- Completely impervious to moisture and will not support mould and mildew growth.
- Will not rot and are unaffected by corrosion, borer or vermin.
- Have a high gloss surface – making it easy to clean
- More stubborn marks can be removed with a non-abrasive domestic cleaner. To remove dirt and soap build up, Fenta can be wiped down periodically with Polycell Sugar Soap or kerosene on a damp cloth.

FIRE PROPERTIES

Fenta Ceiling Tiles have been tested by the Building Research Association of New Zealand (BRANZ) to the testing procedures outlined in ISO 5660: (2002). These determine the Group Number Classification in accordance with New Zealand Building Code (NZBC) Verification Method C/VM2 Appendix A.

For the purposes of compliance Fenta Ceiling Tiles were given the Group Number classification 1-5, the highest level possible in New Zealand Building Code Standards.

Hardiflex, the James Hardie product that Fenta Ceiling Tiles coat with its patented UV technology, will not burn and has the following “Early Fire Hazard Indices” (tested as AS 1530 Part 3 1982).

Ignitability Index	0
Spread of Flame Index	0
Heat Evolved Index	0
Smoke Developed	0

Maximum service temperature for the base sheet and the coating is 105°C

The Early Fire Hazard Indices of the finished painted sheet are as follows:

Spread of Flame	0
Smoke Developed Index	3

MASS AND DIMENSIONS

Fenta Ceiling Tiles Nominal Dimensions and Mass

Tile Length	1195 mm
Tile Width	595 mm
Thickness	4.5 mm and 6.00mm
Approximate Mass at EMC	6.3kg/m ²

Note: all dimensions given are subject to manufacturing tolerances and the thickness given is the bottom of this tolerance range.

HANDLING AND STORAGE

Fenta Ceiling Tiles should be stacked on a smooth level surface. Carry ceiling tiles on edge. It is essential to store under cover and keep dry prior to fixing. Ceiling Tiles are placed in pairs face to face with polythene inter-levers.

INSTALLATION DETAILS

Fenta Ceiling Tiles should be installed in two-way exposed suspended ceiling systems. Exposed Ceiling grid systems must be fully braced to resist seismic forces and the tiles clipped down with a suitable clip. The complete suspension system is to fully comply with the requirements of NZ 4203: 1992 – General Structure Design and Design Loadings for Buildings and NZAS 2785 2000 Suspended Ceiling Design and Installation and/or meet current regulations.

Fenta Ceiling Tiles must be clipped – the minimum clip to be one to each corner of the tile and one in the centre of each long span.

If required, the ceiling tiles can be sealed down to the grid to give positive air and vapor seals using a 10mm x 3mm strip of white Inseal 4254 bonded to the horizontal of the grid. The tile is then clipped down to give a positive seal.

When different heat conditions apply to the underside to the tile and cavity above a fiberglass batt, a minimum of 50mm thick is recommended to help insulate the tile from extreme temperature.

WARRANTY

Fenta Ceiling Tiles come with a 10-year manufacturer's warranty. For full Warranty details please visit www.batessurfaces.co.nz. For more information please phone Bates Surfaces on 0800 269 251.

WHERE TO BUY

Distributor network: Potters, Comfortech and T&R.
